

Silicone X-TREME TAPE® FAMILY OF PRODUCTS



X-TREME TAPE® products are extruded from a special high performance silicone compound under strict ISO Quality Standards.

Self-Fusing... Bonds Only to Itself. If you can wrap it, **X-TREME TAPE®** can fix it!

Stays Flexible to -60°F (-50°C). **Won't Melt** up to 500°F (+260°C).

Insulates up to 8000 Volts with a single .020" thick layer.

Forms an Air and Moisture Tight Seal... quickly and effectively fix, seal or repair virtually anything.

Waterproofs, Weatherproofs and Withstands UV Rays.



Multi-Use Product for Any Retail Department Including Automotive, Plumbing, Electric, Tape/Glue QuikFix for Leaky Pipes, Blown Hoses, Frayed Cords Insulates, Seals, Protects



1" W x 10' Long x .020" Thick
Triangular Profile, Black
Available in Clamshell or
Recloseable Poly Bag Packaging



HVAC, Dryer Vents, Vacuum Hoses, Dust Collectors
Designed to Handle Larger, Tougher Jobs
Wider and Thicker than Original X-Treme Tape
Never Dries Out - Leaves Joints & Hoses Clean when Removed



1 1/2" W x 25' Long x .020" Thick
Rectangular Profile, Gray
Packaged in Folded Carton



Specially Packaged for Marine & Watercraft Markets
Must-Have Repair Wrap to Get You Back to Shore
Forms a Water-Tight Seal, Prevents Corrosion
For Rigging, Wiring and Hoses



1" W x 10' Long x .020" Thick
Triangular Profile, White
Clamshell Package



Unique System to Clamp Woodwork during Glue Drying
Holds Irregular Shapes Traditional Clamps Can't Handle
No Adhesive Residue on Raw or Finished Wood
Self Bonding - Won't Damage Surfaces



1" W x 10' Long x .020" Thick
Triangular Profile, Red-Orange
Clamshell Package



Insulates to 8000 Volts. Class H Insulator. UV Resistant.
Air & Moisture Tight Seal - Better Than Heat Shrink Tubing
No Sticky, Messy Adhesive like Plastic Electrical Tapes
Packaged for Electrical, Cable, Satellite, Wiring and Solar Installation Markets



For use up to 600V and 80°C (176°F)

1" W x 10' Long x .020" Thick
Triangular Profile, Black or Red
1 1/2" W x 10' Long x .020" Thick
Triangular Profile, Black or Red
Clamshell Package



All X-Treme Tape Products Comply to Flammability 16 CFR 1500.44 and CPSC's ASTM F963-8, REACH, RoHS and Prop 65 Standards
409 Parkway Drive · Park Hills, Missouri 63601 · 800-633-6775 · sales@mocap.com · www.XTremeTape.com